

**Pending Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A method of reducing the bit rate of a video bitstream to a meet bandwidth constraint[[s]], the method comprising:  
identifying transform coefficients representing video content in a frame or a portion of frame of the video bitstream; and  
filtering selected transform coefficients from the video bitstream to thereby reduce the bit rate of the video bitstream and produce a reduced bit rate for the video bitstream that meets the bandwidth constraint, wherein the video bitstream before filtering does not meet the bandwidth constraint and the video bitstream including the modified transform coefficients includes the reduced bit rate that meets the bandwidth constraint.
2. (Original) The method of claim 1, wherein filtering selected transform coefficients comprises using a cut-off index.
3. (Original) The method of claim 1, wherein filtering selected transform coefficients comprises using a filter.
4. (Original) The method of claim 3, wherein the filter comprises ones and zeros.
5. (Currently Amended) The method of claim 3, wherein the filter comprises threshold values that determine which transform coefficients are filtered.
6. (Currently Amended) The method of claim 3, ~~wherein the filter is a low-pass filter~~ 1 wherein the method selectively filters fewer transform coefficients for a macroblock according to the number of the macroblock in a frame.
7. (Currently Amended) The method of claim 3, ~~wherein the filter is a band-pass filter~~ 1 wherein the transform coefficients from the video bitstream are filtered differentially on a per block or a per macroblock basis.

8. (Currently Amended) A method of filtering transform coefficients associated with an input bitstream, method comprising:
- identifying transform coefficients associated with an input bitstream;
  - selecting transform coefficients for filtering to provide modified transform coefficients, wherein the transform coefficients associated with the input bitstream are selected differentially on a per block or a per macroblock basis; and
  - generating an output bitstream, wherein the output bitstream associated with modified transform coefficients uses less bandwidth than the input bitstream associated with the transform coefficients.
9. (Original) The method of claim 8, wherein identifying transform coefficients comprises performing variable length decoding on the input bitstream.
10. (Original) The method of claim 8, wherein identifying transform coefficients comprises acquiring the transform coefficients from a file.
11. (Original) The method of claim 8, wherein identifying transform coefficients comprises performing a DCT operation on video data.
12. (Original) The method of claim 8, wherein identifying transform coefficients comprises performing a DCT operation on audio data.
13. (Original) The method of claim 8, wherein the transform coefficients are DCT coefficients.
14. (Original) The method of claim 8, wherein generating an output bitstream comprises performing variable length coding.
15. (Original) The method of claim 8, wherein selecting transform coefficients for filtering comprises identifying a cut-off index.
16. (Original) The method of claim 8, wherein selecting transform coefficients for filtering comprises identifying a filter.
17. (Currently Amended) The method of claim 16, wherein the filter changes on a per block or per macroblock basis ~~comprises zeros and ones.~~
18. (Currently Amended) The method of claim 16, wherein the filter comprises threshold values that determine which transform coefficients are filtered.
19. (Original) The method of claim 16, wherein the filter is 8x8.
20. (Original) The method of claim 16, wherein the filter is a one dimensional array.

21. (Currently Amended) The method of claim 16, ~~wherein the filter is a low-pass filter 8~~ wherein the method selectively filters fewer transform coefficients in a macroblock according to the number of the macroblock in a frame.
22. (Currently Amended) An apparatus for filtering transform coefficients associated with input bits to provide modified transform coefficients associated with output bits, the apparatus comprising:
- an input interface for receiving transform coefficients associated with input bits;
  - a filtering stage coupled to the input interface, wherein the filtering stage selects transform coefficients for filtering; and
  - an output interface coupled with the filtering stage for providing modified transform coefficients associated with output bits, wherein the number of output bits is less than the number of input bits and the filtering produces a bit rate for the modified transform coefficients that meets a bandwidth constraint, wherein the transform coefficients before filtering does not meet the bandwidth constraint and the modified transform coefficients includes a reduced bit rate that meets the bandwidth constraint
23. (Original) The apparatus of claim 22, wherein the input interface comprises a variable length decoder.
24. (Original) The apparatus of claim 22, wherein the input interface reads the transform coefficients from a file.
25. (Original) The apparatus of claim 22, wherein the output interfaces comprises a variable length encoder.
26. (Original) The apparatus of claim 22, wherein the filtering stage uses a cut-off index.
27. (Original) The apparatus of claim 22, wherein the filtering stage uses a filter.
28. (Currently Amended) The apparatus of claim 27, wherein the filter changes on a per block or per macroblock basis ~~comprises zeros and ones.~~
29. (Currently Amended) The apparatus of claim 27, wherein the filter comprises threshold values that determine which transform coefficients are filtered.
30. (Currently Amended) The apparatus of claim 27, ~~wherein the filter is a low-pass filter 22~~ wherein the method selectively filters fewer transform coefficients for a macroblock according to the number of the macroblock in a frame.

31. (Currently Amended) A computer readable medium comprising computer code for filtering transform coefficients associated with an input bitstream, the computer readable medium comprising:

computer code for identifying transform coefficients associated with an input bitstream;

computer code for selecting transform coefficients for filtering to provide modified transform coefficients, wherein the transform coefficients associated with the input bitstream are selected differentially on a per block or a per macroblock basis; and

computer code for generating an output bitstream, wherein the output bitstream associated with modified transform coefficients uses less bandwidth than the input bitstream associated with the transform coefficients.

32. (Original) The computer readable medium of claim 31, wherein identifying transform coefficients comprises performing variable length decoding on the input bitstream.

33. (Original) The computer readable medium of claim 31, wherein identifying transform coefficients comprises acquiring the transform coefficients from a file.

34. (Original) The computer readable medium of claim 31, wherein identifying transform coefficients comprises performing a DCT operation on video data.

35. (Original) The computer readable medium of claim 31, wherein identifying transform coefficients comprises performing a DCT operation on audio data.

36. (Original) The computer readable medium of claim 31, wherein the transform coefficients are DCT coefficients.

37. (Original) The computer readable medium of claim 31, wherein generating an output bitstream comprises performing variable length coding.

38. (Original) The computer readable medium of claim 31, wherein selecting transform coefficients for filtering comprises identifying a cut-off index.

39. (Original) The computer readable medium of claim 31, wherein selecting transform coefficients for filtering comprises identifying a filter.

40. (Currently Amended) An apparatus for reducing the bit rate of a video bitstream to meet bandwidth constraints, the method comprising:

means for identifying transform coefficients representing video content in a frame or a portion of frame of the video bitstream; and

means for filtering selected transform coefficients from the video bitstream to thereby reduce the bit rate of the video bitstream and produce a reduced bit rate for the video

Appl. No.: 09/867,966

5

Atty Docket: CISC219/4103

bitstream that meets the bandwidth constraint, wherein the video bitstream before filtering does not meet the bandwidth constraint and the video bitstream including the modified transform coefficients includes the reduced bit rate that meets the bandwidth constraint

41. (Original) The apparatus of claim 40, wherein filtering selected transform coefficients comprises using a cut-off index.
42. (Original) The apparatus of claim 40, wherein filtering selected transform coefficients comprises using a filter.
43. (Original) The apparatus of claim 42, wherein the filter comprises ones and zeros.
44. (Currently Amended) The apparatus of claim 42, wherein the filter comprises threshold values that determine which transform coefficients are filtered.
45. (Currently Amended) The apparatus of claim 42, ~~wherein the filter is a low-pass filter~~ 40 wherein the method selectively filters fewer transform coefficients for a macroblock according to the number of the macroblock in a frame.
46. (Currently Amended) The apparatus of claim 42, ~~wherein the filter is a band-pass filter~~ 40 wherein the transform coefficients from the video bitstream are filtered differentially on a per block or a per macroblock basis.